

CML-MPPT (10 A)

Solar Charge Controller with Maximum Power Point Tracker Technology



- SMD assembly, greater reliability
- New housing design
- High current rated MOSFETs
- High performance micro controller
- More intuitive LED design
- USB port for charging mobile phones or small music players
- Easily accessible terminals
- Easy mounting

The CML-MPPT charge controller are equipped with a number of outstanding features such as a status display, alarm, and safety functions.

The temperature-compensated, four-stage charging algorithm (float-main-boost-equalization) is adjustable for sealed and vented lead-acid batteries.

The CML-MPPT charge controller also allows either a SOC or voltage-controlled low-voltage disconnect.

The use of MPPT technology can contribute to a considerable boost in energy output from PV modules (up to 30% more), specially in moderate/colder climate areas where PV module voltages tend to be higher.

Battery status is clearly indicated by three LEDs. An acoustic alarm warns about an impending low-voltage disconnect (LVD).

CML-MPPT (10 A)

Solar Charge Controller with Maximum Power Point Tracker Technology

| Type | CML-MPPT 10 |
|--|--|
| System voltage | 12/24 V auto recognition |
| Max. charge/load current | 10 A |
| Float charge | 13.8/27.6 V (25 °C) |
| Main charge | 14.4/28.8 V (25 °C), 0.5 h (daily) |
| Boost charge | 14.4 /28.8 V (25 °C), 2 h Activation: battery voltage < 12.3/24.6 V |
| Equalization | 14.8/29.6 V (25 °C), 2 h Activation: battery voltage < 12.1/24.2 V |
| Deep discharge protection: | |
| State-of-charge dependent | 11.4 – 11.9 V / 22.8 – 23.8 V by SOC |
| Voltage dependent | 11.0/22.0 V by voltage |
| Reconnect level | 12.8/25.6 V |
| Overvoltage protection | 15.5/31.0 V |
| Undervoltage protection | 10.5/21.0 V |
| Max. panel voltage | 30 V in 12 V system 50 V in 24 V system |
| Temperature compensation (Charge voltage) | –25 mV/K at 12 V –50 mV/K at 24 V |
| Self-consumption | < 10 mA |
| Grounding | Positive grounding |
| Ambient operating temperature | –40 to +50 °C |
| Max. altitude | 4,000 m above sea level |
| Battery type | Lead acid (GEL, AGM, flooded) |
| USB port | 5.0 V; 800 mA |
| Wire cross section | max. 16,0 mm ² (AWG 6) |
| Weight | 260 g |
| Dimensions (W x H x D) | 120 x 120 x 34 mm |
| Type of protection | IP20 |